



Riviera

505 555 605

Standard Features

Hypalon 2-tone white and ivory tubes, wear patches, single rubbing strake
 Deep V hull, monocoque construction
 Custom carbon lay-up
 Splashwell including drains, hull drains
 Integral sculpted rear seat with bolster backrest and large storage area
 Bow eye, 2 transom U bolts, anchor eye
 90 litres underdeck fuel tank
 Bow seat with cushion and locker beneath
 Upright console with front seat and cushion
 Bolster helm seat
 A-frame with navigation lights, port & starboard, boarding platform with teak
 Bow step with teak
 Stainless steel flush mount bow cleat, bow U bolt
 2 stainless steel rear flush mount cleats
 White upholstery with a choice of piping or panelling in ivory
 Stainless steel davit lifting eyes, 3 or 4 point
 Hand pump, repair kit, owner's manual

Accessories

Teak decking
 2-man jockey seats
 1-man jockey seats
 Individual backrests for sculpted rear seat
 Swing back helm seat
 Bimini cover
 Mooring cover
 Boarding platform with telescopic ladder
 Hydraulic steering

Technical Specifications

	505	555	605
Overall Length	5.00m	5.50m	6.00m
Internal Length	4.05m	4.55m	5.05m
Overall Width	2.28m	2.28m	2.28m
Inside Width	1.38m	1.38m	1.38m
Tube Diameter	0.46m	0.46m	0.46m
Number of Air Chambers	5	5	5
Number of Persons	8	10	12
Maximum Payload	765kg	1000kg	1100kg
Boat Weight Std Spec	410kg	450kg	520kg
Maximum Power	80hp	100hp	120hp
Engine Shaft	L	L	L
Design Category	C	B	B
Boat Weight inc Eng/Rigging	750kg	793kg	890kg
Boat & Trailer Weight	1150kg	1193kg	1290kg
Trailer Weight	400kg	400kg	400kg
Height on Trailer	2.35m	2.35m	2.35m
Height of Boat	1.80m	1.80m	1.80m
Engine Weight	170kg	170kg	200kg
Prop Size	19"	19"	19"
Draft in Water at Rest	0.47m	0.47m	0.47m
Max Speed	32knts	35knts	40knts

Ribtec carries out a continuous program of product improvement and safety awareness. Specifications are subject to change without notice, although all details are correct at the time of going to press. Ribtec products may be produced with a different trim level than originally specified. All dimensions are +/- 3%.

Please note that performance of your boat depends on engine size, propeller selection, trim settings, payload distribution and operating conditions. Refer to sections within this manual and within your engine owner's manual to obtain the best performance from your Ribtec.

Ribtec Ltd, Collingwood Road, Townstal, Dartmouth, Devon TQ6 9JY
 E: sales@ribtec.co.uk T: 01803 832060 F: 01803 839090